



BEARING Argentina



Deep Groove Ball Bearing Distributor of NSK SKF NTN Koyo 6206 6207 6208 6209 2RS

Bearing No. 6206

6206 Bearing 2D drawings and 3D CAD models

| | |
|-------------------------------|--------------------------|
| Size | 30x62x16 mm |
| Bore Diameter | 30 mm |
| Outer Diameter | 62 mm |
| Width | 16 mm |
| d | 30 mm |
| D | 62 mm |
| B | 16 mm |
| C | 16 mm |
| r min. | 1 mm |
| da min. | 35 mm |
| Da max. | 57 mm |
| ra max. | 1 mm |
| Weight | 0,199 Kg |
| Basic dynamic load rating (C) | 19,5 kN |
| Basic static load rating (C0) | 11,3 kN |
| (Grease) Lubrication Speed | 11000 r/min |
| (Oil) Lubrication Speed | 13000 r/min |
| Category | Single Row Ball Bearings |
| Inventory | 2.0 |
| Manufacturer Name | KOYO |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.217 |
| EAN | 0605790060847 |
| Product Group | B00308 |
| Enclosure | Open |



BEARING Argentina

| | |
|---------------------------------|--|
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Internal Clearance | C0-Medium |
| Inch - Metric | Metric |
| Long Description | 30MM Bore; 62MM Outside Diameter; 16MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features |
| Category | Single Row Ball Bearing |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer URL | http://www.koyousa.com |
| Manufacturer Item Number | 6206 |
| Weight / LBS | 0.477 |
| Outside Diameter | 2.441 Inch 62 Millimeter |
| Bore | 1.181 Inch 30 Millimeter |
| Outer Race Width | 0.63 Inch 16 Millimeter |
| Bearing No. | 6206 |
| r(min) | 1 |
| Cr | 24.3 |
| C0r | 11.3 |
| Cu | 0.800 |
| f0 | 13.9 |
| Grease lub. | 11000 |
| | |



BEARING Argentina

| | |
|------------------|-------|
| Oil lub. | 13000 |
| da(min) | 35 |
| Da(max) | 57 |
| ra(max) | 1 |
| (Refer.)Mass(kg) | 0.199 |